



Material Safety Datasheet

CAS No 16592-5-80-5
Date Issued: 2011/08/26
TRAMISOL PLUS

Company Details

| | | | |
|----------------|-------------------------------------|----------------------|-----------------|
| <u>Name</u> | Afrivet Business Management(Pty)Ltd | <u>Emergency Tel</u> | 0860833278 |
| <u>Address</u> | P.O Box 2009 Faerie Glen 0043 | <u>Tel</u> | +27(0)129916416 |
| | | <u>Fax</u> | +27(0)129916417 |

1. Product and Company Identification

| | | | |
|--------------------------------|--|---------------------|-----|
| <u>Trade / Commercial Name</u> | TRAMISOL PLUS | | |
| <u>Chemical Name</u> | toxic liqs, organic NOS | | |
| <u>Formula</u> | Levamisole HCL , Rafoxanide | | |
| <u>Chemical Family</u> | Toxic, Liquid, Organic, N.O.S (Levamisole HCL) | | |
| <u>Synonyms</u> | | | |
| <u>Un No</u> | 2810 | <u>Hazchem Code</u> | 3xe |
| <u>ERG No</u> | 153 | <u>EAC</u> | 55 |

2. Hazards Identification

Toxic
Contact with liquid causes severe damage: to skin, to eyes.
The vapour has irritant effect: on eyes, on air passages.
May evaporate quickly.
The vapour may be invisible. The vapour is heavier than air and spreads along ground.

3. Composition

Hazardous Components toxic liqs, organic NOS

4. First Aid Measures

| | |
|-----------------------------|---|
| <u>First Aid Skin</u> | Remove & isolate contaminated clothing and shoes. For minor skin contact, avoid spreading material on unaffected skin. Flush body with plenty of water for at least 20 minutes. Keep warm and quiet. |
| <u>First Aid Eyes</u> | Flush eyes with water for 20 minutes. Hold eyelids open while washing. |
| <u>First Aid Ingested</u> | Do not induce vomiting. Seek medical assistance. |
| <u>First Aid Inhalation</u> | Move victim to fresh air. If not breathing give artificial respiration. Do not use mouth-to-mouth, if victim has inhaled or ingested the substance; induce artificial respiration with the aid of a pocket mask with a one-way valve. If breathing of victim is difficult administer oxygen. Effects of exposure may be delayed. |

5. Fire Fighting Measures

Small Fires: Dry chemical, CO2 or water spray.
Large Fires: Dry chemical, CO2, alcohol-resistant foam or water spray.
Move containers from fire area if you can do it without risk.

Dike fire control water for later disposal; do not scatter the material.
 Fire involving Tanks or Bulk Containers: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
 Do not get water inside containers. ALWAYS stay away from the ends of tanks.
 Cool containers with flooding quantities of water until well after fire is out.
 Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
 Isolate spill or leak area immediately for at least 25 to 50 metres (80 to 160 feet) in all directions.
 Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate enclosed areas.
 Wear positive pressure self-contained breathing apparatus (SCBA).
 Wear chemical protective clothing which is specifically recommended by the manufacturer.
 Structural firefighters' protective clothing is recommended for fire situations ONLY; it is not effective in spill situations.
 If ROAD OR RAIL TANKER is involved in a fire, ISOLATE for 800 metres (1/2 mile) in all directions;
 also, consider initial evacuation for 800 metres (1/2 mile) in all directions.

6. Accidental Release Measures

Full protective clothing including breathing apparatus
 Contain (avoid spillage from entering drains or water courses)
 PRECAUTIONS:
 Restrict access to area.
 Provide adequate protective equipment and ventilation.
 Remove sources of heat and flame.
 Notify occupational and environmental authorities.
 SPILL OR LEAK:
 ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
 Stop leak if you can do it without risk.
 Prevent entry into waterways, sewers, basements or confined areas.
 Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
 DO NOT GET WATER INSIDE CONTAINERS.

7. Handling And Storage

Separation of at least 3M from the following classes is recommended.
 Corrosives
 Fire separation of at least 5M or 4Hr fire resistant wall
 from the following classes is recommended.
 Flammable Gases Flammable Liquids
 Flammable Solids Spontaneously Combustibles
 Dangerous When Wet Oxidizing Agents
 Storage in the same room or space is prohibited with the following classes:
 The rooms or spaces should be at least 10M apart.
 Explosives Organic Peroxides

8. Exposure Controls/Personal Protection

| | |
|-------------------------------------|--|
| <u>Occupational Exposure Limits</u> | T W A OEL-RL SHORT TERM OEL-RL ----- PPMa) MG/M3b) PPMa) MG/M3b) ----- 0.2 5 - 5 |
|-------------------------------------|--|

| | |
|-----------------|--|
| <u>Controls</u> | The control measures appropriate for a particular worksite depend on how this material is used and on the extent of exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. |
|-----------------|--|

Use a non-sparking, grounded ventilation system separate from other exhaust ventilation systems. Exhaust directly to the outside.
Supply sufficient replacement air to make up for air removed.
Have a safety shower/eye wash fountain readily available in the immediate work area

Personal Protection

If engineering controls and work practices are not effective in controlling this material, then wear suitable personal protection equipment, including chemical safety goggles & face shield, boots, imperious gloves, coveralls, & respiratory protection.
Have appropriate equipment available for use in emergencies.

9. Physical & Chemical Properties

Toxic liquid , light in colour, slight odour

Boiling point: weighted average 103 C

Melting Point may solidify at < 1 C , weighted average : 0.05 C

Soluble easily soluble in methanol , acetone , slightly soluble in diethyl ether
insoluble in cold/ hot water and n-octanol

10. Stability And Reactivity

Conditions to Avoid Stable.

Incompatible Materials Reactive with oxidizing agents , slightly reactive to Alkalis

Other slightly explosive in the presence of open flames , sparks and static electricy

11. Toxicological Information

TOXIC; inhalation, ingestion, or skin contact with material may cause severe injury or death.

Contact with molten substance may cause severe burns to skin and eyes.

Effects of contact or inhalation may be delayed.

Acute toxicity LD50 rat 180mg/kg

12. Ecological Information

The substance is toxic to aquatic organisms.

It is strongly advised that this substance does not enter the environment.

13. Disposal Considerations

Disposal Method Product There are no uniform EC regulations for the disposal of chemicals or residues.
Chemical residues generally count as special waste.
The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations.
We recommend that you contact the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste.

Disposal Method Packaging Disposal in accordance with local legal provisions.

14. Transport Information

| | | | |
|---------------------------|-------------------------------|---------------------|-----|
| <u>UN No</u> | 2810 | <u>Hazchem Code</u> | 3xe |
| <u>ERG No</u> | 153 | <u>EAC</u> | 55 |
| <u>IMDG-Shipping Name</u> | TOXIC LIQUID, ORGANIC, N.O.S. | | |

| | | | |
|-------------------------|-----------------------------------|-----------------------------|----------|
| <u>IMDG Code</u> | 6.1 | <u>IMDG-Packaging Group</u> | I/II/III |
| <u>Marine Pollutant</u> | Yes | | |
| <u>Class</u> | Class: 6.1 Poison Group: I/II/III | | |
| <u>Subsidiary Risks</u> | None | | |

| |
|-----------------------------------|
| 15. Regulatory Information |
|-----------------------------------|

| | |
|----------------------------------|--|
| <u>EEC Hazard Classification</u> | 6.1 |
| <u>Risk Phases</u> | R23 Toxic by inhalation. R24 Toxic in contact with skin. R25 Toxic if swallowed. R52 Harmful to aquatic organisms. R53 May cause long-term adverse effects in the aquatic environment. |
| <u>Safety Phases</u> | S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36 Wear suitable protective clothing. S37 Wear suitable gloves. S39 Wear eye / face protection. S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.) S61 Avoid release to the environment. Refer to special instructions / safety data sheets. |

National Legislation

| |
|------------------------------|
| 16. Other Information |
|------------------------------|

Reason for Alteration: General update.

The information contained herein is based on the present state of our knowledge.
It characterizes the product with regard to the appropriate safety precautions.
It does not represent a guarantee of the properness of the product.

Disclaimer:

 The company provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.
 THE COMPANY MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, THE COMPANY WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

LAST PAGE

| |
|--|
| All information is given in good faith but without guarantee in respect of accuracy & no responsibility is accepted for errors or omissions or the consequences thereof. |
|--|